


Technical Data Sheet

GLOUROS-Natural Siding & Masonry Cleaner No. 1806

Application range	For interior and exterior wooden- and stone surfaces such as tiles, gravestones, walls, and facades. Not suitable for marble, calcareous stone or other material sensitive to acid e.g. terrazzo.
Technical qualities	Removes chalk- and cement residue, moss, algae, stains of fungi, salt deposits on facades. Dissolves oil, grease- and protein soiling, completely or partly, depending on the surface.
Full declaration	Water, citric acid, Reetha extract.
Dilution	Depending on the density and the amount of soil, dilute with water at the ratio of 1:10 (1 part product, 10 parts water) for cleaning and at the ratio of 1:5 (1 part product, 5 parts water) for after-treatment.
Application method	With a sponge, a spray bottle, or a high pressure cleaner.
Cleaning	Clean tools immediately after use with plenty of water.
Specific gravity	1.09 g/ml.
Safety advice	 <p>H319 Causes serious eye irritation. P102 Keep out of the reach of children. P280 Wear protective gloves/protective clothing/eye protection/face protection. Warning P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. P337+P313 If eye irritation persists: Get medical advice/attention.</p> <p>The surfactants used are in accordance with the regulation for detergents No. 648/2004 biodegradable. Non-ionic surfactants: less than 5%.</p>
Disposal	According to locally regulated laws.
Container sizes	1.0 l; 10 l; 30 l.
Storage	Shelf life: unopened at least 4 years. See reverse for application instructions.

How to use

GLOUROS-Natural Siding & Masonry Cleaner No. 1806

Application	Apply with a sponge or a spraying device on the objects or surfaces to be treated. Rub the dirt off with a non-abrasive pad (normally white) or a sponge and flush or rinse with plenty of water.
Fungi, moss, algae	Apply GLOUROS No. 1806 at a ratio of 1: 10. To protect the surface against new fungi spray again with a dilution of 1: 5 and allow to dry.
Salt deposits on facades	The surface should be watered well. Spray surface with a dilution of 1: 20. Rinse off with plenty of water and low pressure.
Metals	Clean light mineral soiling on brass, copper and stainless steel with a dilution of 1: 5 to 1: 20. Select for chalk deposits on chrome surfaces a dilution of 1: 5.
Wood	Dilute GLOUROS No. 1806 with water 1: 10 and spray on, scrub the dirt with a non-abrasive pad (normally white) or a sponge until the dirt dissolves, then rinse. Afterwards spray on the surface diluted 1: 5 and let dry. If the old paint is weathered, the surface should be post-treated with LIVOS-products. Please check the wood moisture recommended for each product. If the paint is weathered down to the bare wood, a rebuild is necessary with a LIVOS-paint system.
Important tips	The reaction time depends on the density and the age of the soiling. Always do a test application to check the surface's compatibility with GLOUROS No. 1806 and observe the effect.

These directions are the result of long years of research and practical testing. They are backed by our most current expert information. New findings may invalidate this information. The latest version is available on our website at www.livos.de. This data sheet is meant to serve as information and instruction. No legal liability should be interpreted from it. In case of doubt, please contact the retailer, wholesaler, or manufacturer.

July 2018