

Technical Data Sheet

VEDO Wall Filler No. 440

N means **LIVOS neutral** for the allergy-prone and chemically sensitive

Without orange oil

Range of application	Interior use only. For repairing and filling cracks, holes and irregularities on plastered surfaces, masonry and concrete. Suitable for artistic modeling purposes. Not suitable for floors.
Technical qualities	Powdery, fine and excellent consistency.
Full declaration	Gypsum, methyl cellulose, citric acid, cellulose.
Preparation	Surface must be free of dust, grease and loose materials. Concrete should be moistened just before the application with a wet sponge. Non absorbent and smooth surfaces need to be well roughened.
Application method	Pour 2 parts of filler into 1 parts of water, stir well and use mixture within 1- 1.5 hours. For filling large surfaces add a bit more water. The applied material can be smoothed immediately after application using water and smoothing trowel or sponge. After drying it can be slightly sanded. The maximum layer thickness should not exceed 2mm.
After treatment	Priming with GRAVA Wall Primer Sealer No. 408 and application of LIVOS Wall and Dispersion Paints No. 412 or No. 413 as well as DUBRON Natural White Plaster No. 465.
Drying time	Depending on surface, thickness and room temperature: 2 - 8 hours.
Container sizes	1 kg; 5 kg; 10 kg; 25 kg.
Storage	Dry and tightly closed. Shelf life: at least 4 years. Keep out of the reach of children.
Disposal	According to locally regulated laws.

These directions are the result of long years of research and practical testing. They are backed by our most current expert information. New findings may invalidate this information. The latest version is available on our website at www.livos.de. This data sheet is meant to serve as information and instruction. No legal liability should be interpreted from it. In case of doubt, please contact the retailer, wholesaler, or manufacturer.

April 2016