

Technical Data Sheet

REMIO Natural Stain Blocking Primer No. 618

Range of application	For all interior absorbent mineral walls and ceilings as well as wood-based materials such as OSB and hardboards.
Technical qualities	White pigmented, fast drying. Good adhesion to the surface. Prevents the penetration of colored impurities caused by water, nicotine etc. Free of organic chemical compounds according to DIN EN 71, part 9.
Full declaration	Chalk, water, isoaliphates, linseed oil - stand oil - natural resin ester, titan dioxide, dammar resin, micronized wax, bentonite, dehydrated amino sugar, soy lecithin, lemon oil and drying agents free of lead (Ca, Mn, Zr).
Color	White.
Dilution	Ready to use.
Preparation	The surface must be dry, solid, clean and free of grease, resin and dust. Holes should be filled with suitable materials, e.g. VEDO Wall Filler No. 440 or for wood ANAVO Natural primer No. 628.
Application method	Remove possible skin formed on surface and stir thoroughly. Application by brush, roller or spray application with suitable devices. Can be painted over with LIVOS wall paint, such as DUBRON Natural Dispersion Paint No. 412 / 465, ELERKOS No. 168 / 169, STRUTIVOS Marble Pit Lime Paint No. 475, CANTO Natural Matt Paint No. 692 and VINDO Natural Gloss Paint No. 629.
Coverage	1 undiluted liter is sufficient for approximately 10m ² (107.6 ft ²), i.e. 100 ml/m ² . Determine exact values by doing a test application. Each dried coating layer may not exceed 50µm.
Specific gravity	Approximately 1.29 g/ml.
Drying time	At 23°C (73.4°F) and 50% relative humidity, dry to the touch after appr. 3 hours. Dry, sand-able and ready for subsequent coating after appr. 48 hours.
Clean up	Clean tools immediately after use with SVALOS Thinner No. 222 or LEVO Brush Cleaner No. 997.
Safety advice	<p>Ensure good ventilation during and after application. Always be sure to store and then dispose cleaning cloths, sponges, etc. that are still wet or even slightly moist with REMIO Stain Blocking Primer No. 618 in an airtight metal container or in water. As there is a danger of spontaneous combustion caused by the plant oil content in the product. The liquid or applied product is not self-ignitable.</p> <p>P102 Keep out of reach of children. P301+P310 IF SWALLOWED: Rinse mouth. Do NOT induce vomiting. Immediately call a doctor. EUH208 Contains lemon oil (limonene). Can cause allergic reactions. Emergency number: +49 (0)6132-84463 (24 hrs - GBK GmbH)</p>
Disposal	According to locally regulated laws.
Container sizes	0.05 l; 0.75 l; 2.5 l; 10 l; 30 l.
Storage	Cool and dry. Shelf life: unopened at least 4 years. Close lid of opened container tightly.

These directions are the result of long years of research and practical testing. They are backed by our most current expert information. New findings may invalidate this information. The latest version is available on our website at www.livos.de. This data sheet is meant to serve as information and instruction. No legal liability should be interpreted from it. In case of doubt, please contact the LIVOS customer service.

July 2023