

## Technical Data Sheet

# AMELLOS Wicker Fence Paint No. 673

|                            |  |                                   |
|----------------------------|--|-----------------------------------|
| <b>Application range</b>   | In the outdoor area, for the treatment of untreated wicker fences.   |                                   |
| <b>Technical qualities</b> | Very high yield. After 2 <sup>nd</sup> application semi-glossy and opaque surface. Free of organic chemical compounds according to DIN EN 71, part 9.  |                                   |
| <b>Full declaration</b>    | Depending on the color: Isoaliphates, linseed oil, linseed oil - stand oil, mineral pigments, linseed oil - stand oil - natural resin ester, linseed oil - wood oil - stand oil, chalk, talcum, silicic acid, dehydrated castor oil, dehydrated amino sugar, and drying agents free of lead (Zr, Mn).  |                                   |
| <b>Colors</b>              | 050 Reed green<br>071 Light brown<br>101 Black<br>All colors are intermixable.   | 051 Swedish red<br>081 Dark brown |
| <b>Application method</b>  | By brush or spraying device (dilute with max. 10% SVALOS Spray Thinner No. 222) at temperatures above 12°C (54°F).   |                                   |
| <b>Coverage</b>            | Determine exact coverage by doing a test application.<br>One liter (1.06 quart) is sufficient for approximately 20 to 25 m <sup>2</sup> (215 to 269 ft <sup>2</sup> ), i.e. 44 ml/ m <sup>2</sup> per coat.  |                                   |
| <b>Drying time</b>         | At 23 °C (73 °F) and 50% relative humidity: subsequent coats can be applied after 24 hours. At lower temperatures and higher humidity up to 48 hours. At higher temperatures, please consider shorter drying times.  |                                   |
| <b>Cleaning</b>            | Clean tools immediately after use with SVALOS Thinner No. 222 or LEVO Brush Cleaner No. 997.   |                                   |
| <b>Specific gravity</b>    | Approximately 0.96 g/ml  |                                   |
| <b>Safety advice</b>       | <p>Ensure good ventilation during and after application.</p> <p>Always be sure to store and then dispose of cleaning cloths, polishing pads, sponges, etc. that are still wet or even slightly moist with AMELLOS Wicker Fence Paint No. 673 in an airtight metal container or in water, as there is a danger of spontaneous combustion caused by the plant oil content. The liquid or applied product is not self-ignitable.</p> <p>P102                      Keep out of reach of children.<br/>P301+P310              IF SWALLOWED: Rinse mouth. Do NOT induce vomiting. Immediately call a doctor.</p> |                                   |
| <b>Disposal</b>            | According to locally regulated laws.   |                                   |
| <b>Container sizes</b>     | 0.05 l; 0.75 l; 2.5 l.   |                                   |
| <b>Storage</b>             | Cool and dry. Shelf life: unopened at least 4 years. Paints in opened containers react with oxygen. The less oil is still there, even more so. Residues should be transferred into smaller containers.   |                                   |

## How to use

# AMELLOS Wicker Fence Paint No. 673

|                       |   |
|-----------------------|---|
| <b>Preparation</b>    | The wicker fence must be dry (less than 15% wood moisture content), solid, and free of grease and dust. Priming is not necessary.   |
| <b>Application</b>    | Remove possible skin formed on surface and stir thoroughly before use. As a general rule, apply two thin coats that should be done within a period of 4 weeks.  |
| <b>Care</b>           | According to the need, but at least once a year cleaning with GLOUROS Natural Siding and Masonry Cleaner No. 1806 and after drying, apply a coat of AMELLOS No. 673 (diluted with 10% SVALOS Thinner No. 222).  |
| <b>Important tips</b> | <p>AMELLOS Wicker Fence Paint No. 674 contains little solvent; this may cause a skin formation. Remove skin before use.</p> <p>When AMELLOS Wicker Fence Paint has been used, subsequent coatings should also be done with AMELLOS Wicker Fence Paint. Because of the high elasticity of AMELLOS, other paint tends to flake.</p> <p>AMELLOS Wicker Fence Paint No. 674 does not contain fungicides, i.e. there is a risk of fungal growth. Their appearance depends on the surface roughness, sun- and weather side, moisture content, and natural cover etc.</p> <p>Possible fungi growth should be removed with GLOUROS Natural Siding and Masonry Cleaner No. 1806. Too high coating thickness will lead to wrinkles.</p> |

These directions are the result of long years of research and practical testing. They are backed by our most current expert information. New findings may invalidate this information. The latest version is available on our website at [www.livos.de](http://www.livos.de). This data sheet is meant to serve as information and instruction. No legal liability should be interpreted from it. In case of doubt, please contact the LIVOS customer service (see page 1).

June 2023