

Technical Data Sheet

ALBANTO Cork Paint No. 775

Application range	Inside, as a primer for cork on walls floors.			
Technical qualities	Decorative, elastic, vapor permeable. Solvent-free. Revitalizes the natural surface structure. Free from organic chemical compounds according to DIN EN 71 part 9.			
Full declaration	Depending on color in different proportions: water, mineral pigments, cellulose, corn oil, sodium benzoate.			
Color	011 Corn yellow 111 Green	034 Red 115 Dark green	051 Oxide red 134 Pink	101 Black 202 Cream
Application method	Always stir thoroughly before and during application. One coat maximum at temperatures above 12°C and low humidity. Spread with nylon or foam roller in different directions. Further treatment with ALBANTO Natural Cork Finish No. 799 for higher durability and abrasion resistance.			
Coverage	1l is sufficient for 16 - 20 m ² , that is 56 ml / m ² . Could be considerably less or more depending on the absorbency of the surface.			
Cleaning	Clean equipment immediately after use with hot water and dishwashing liquid.			
Drying time	At 23°C (73°F) and 50% relative humidity, the subsequent coat may be applied after 12 hours.			
Specific gravity	1.05 g/ml (possible deviations depending on the color).			
Safety advice	P102 Keep out of reach of children. Ensure good ventilation during and after application.			
Disposal	According to locally regulated laws.			
Container sizes	0.05 l; 1 l; 2.5 l.			
Storage	Cool and dry. Shelf life: unopened at least 1 year. Storage in the refrigerator extends the shelf life. Close opened containers tightly after use.			
Packaging	Made of polyethylene (PE). This material is ground water neutral and recyclable.			

How to use

ALBANTO Cork Paint No. 775

Preparation

The surface must be dry, solid, absorbent, clean and free of dust.

ALBANTO Cork Paints N° 775 are intensive solid colors. For making them less intensive, dilute with ALBANTO Natural Cork Color Binder N° 778. Thereby add the Binder to the Cork Paint while stirring and mix until the color is homogeneous.

Create a color sample on an identical cork surface!

Application

If a large surface shall be colored, treat wet in wet, square meter after square meter, or work quickly in a team of two persons in order to prevent a quick drying and visible patches.

Graphical patterns can be achieved through application of foils. Stick the foil to the cork surface. Cut the desired pattern with a cutter knife deep into the cork. Take off the foil from the areas to be colored and apply the paint with a roller. After staining immediately take off the remaining foil.

Another possibility is the **coloring of individual cork plates** before their installation. Thereby apply and spread out the ALBANTO Cork Paint evenly with a roller. A post-treatment with ALBANTO Natural Cork Finish N° 799 is possible.

Important tips

The different shades of brown of individual cork plates may not be equalized when applying bright colors. Coarse cork shall be pre-sanded with 180 grit sandpaper. Operate systematically and grind path-wise.

These directions are the result of long years of research and practical testing. They are backed by our most current expert information. New findings may invalidate this information. The latest version is available on our website at www.livos.de. This data sheet is meant to serve as information and instruction. No legal liability should be interpreted from it. In case of doubt, please contact the LIVOS customer service (see page 1).

November 2021